



SUIFED T
SOFIMA

SUIFED T
SOFIMA

SUIFED T
SOFIMA





GAF'S COMING

2 24 83

INSULATION LINER

GAF'S COMING





SD-2601(BK)
COMPONENT DISPLAY
NET WEIGHT 41.0kg 90.4lbs
GROSS WEIGHT 46.0kg 101.4lbs

500V





OSB

SIDE DOWN
EN VERSUS

SPACE JOIST 1/8"
ESPACER LES
BOIS DE 1/8"

NEVER NAIL INTO
JOIST'S
SIDE OR END
NUNCS NAILER

CONSTRUCTION INFORMATION
DO NOT USE FOR
EXTERIOR WALL APPLICATIONS

OSB 424













GREENGLASS
FIBERGLASS
BUILDING

FIBERGLASS
BUILDING

TYPICAL

TYPICAL



238
91155000
hond.com

For more information, visit us online at www.hond.com.
For more information, visit us online at www.hond.com.
For more information, visit us online at www.hond.com.















Vertical black pipe

R-53

Insulation
Fiberglass
Blanket
Insulation
5/8"

PIPE WITH WINDING AND ONLY CONNECT ONLY. SEE NOTES ON P. 1.













This insulation will
LEFT EXPOSED. Special
along close to the frame
is non-combustible.

1/4
INSTALL

ING
AS

Warning: The surface burns. Do not leave exposed for long periods of time. Do not use as a surface for walking or standing. Do not use as a surface for painting or staining. Do not use as a surface for hanging clothes. Do not use as a surface for hanging pictures. Do not use as a surface for hanging plants. Do not use as a surface for hanging anything else.







OCK
H
12

51 52 53
48 49 50 51 52 53
43 44 45 46 47 48 49 50 51 52 53
41 42 43 44 45 46 47 48 49 50 51 52 53

13

13

EcoTouch™
PureFiber® Technology

R-13

EcoTouch™
PureFiber® Technology

R-13

Caution: This facing will burn. Do not leave exposed. Facing must be installed in substantial contact with an approved ceiling, floor or wall material. Keep open flame and other heat sources away from facing.
Precaución: Este revestimiento puede incendiarse. No lo deje expuesto. Esta superficie de papel con capa de kraft se colocará de manera que esté en contacto total con el techo, el piso o la pared aprobada. Manténgala alejada de flamas o de otro tipo de fuente de calor.

Caution: This facing will burn. Do not leave exposed. Facing must be installed in substantial contact with an approved ceiling, floor or wall material. Keep open flame and other heat sources away from facing.
Precaución: Este revestimiento puede incendiarse. No lo deje expuesto. Esta superficie de papel con capa de kraft se colocará de manera que esté en contacto total con el techo, el piso o la pared aprobada. Manténgala alejada de flamas o de otro tipo de fuente de calor.

ECOTOUCH™
PINK® INSULATION

EcoTouch™
PureFiber® Technology







Ecotouch
PureFiber Technology

ECOTOUCH™
PINK® INSULATION
OWENS CORNING



B 10/16/14 FGI-3 13:31

ECOTOUCH™
PINK® INSULATION
OWENS CORNING

Ecotouch
PureFiber Technology

R-13

OWENS CORNING
Build
INSIDE

R-19



424



